

Critical Apparatus Ontology

–

Adding Semantics to XML/TEI Documents



Diego Canali for TALOS – AI4SSH

ERA Chair in Artificial Intelligence for Humanities and Social Sciences

Rethymno, 6 November 2023



Critical Apparatus Ontology

Ontology Specification Draft

Release 08.07.2019

IRI: <https://w3id.org/cao>

Current version: 0.9


Authors: Francesca Giovannetti

Imported Ontologies and models:

- *hico*
- *frbr*
- *naryparticipation.owl*
- *participation.owl*
- *situation.owl*
- *timeinterval.owl*
- *cpannotationschema.owl*
- *oa#*



1. Introduction





2. Description

- The Critical Apparatus Ontology (CAO) is an OWL 2 DL ontology for representing the apparatus of textual variants and philological arguments that accompanies a digital critical edition.
- It allows to express **RDF data** within an **.xml document** through **formal syntaxes** such as:
 - **RDF/XML**: <https://www.w3.org/TR/rdf-syntax-grammar/>
 - **Turtle**: <https://www.w3.org/TR/rdf12-turtle/#abstract>
 - **JSON-DL**: <https://www.w3.org/TR/json-ld11/>
- In this presentation, along with **F. Giovannetti's** practice, I will use **Turtle** syntax to provide examples.




2. Description

- How to represent the critical apparatus using the CAO model:
 - From the creation of a new apparatus entry
 - To the description of the readings and their relationships
 - To the formalization of the process of scholarly interpretation.



2.1. Creation of a new apparatus entry



Web Annotation Ontology


(<https://www.w3.org/TR/annotation-vocab/>)

- Body
- Target
- Creator
- Date of Creation

“provenance”



2.2. the body of the annotation: the apparatus entry



| Domain | Property | Range |
|-------------------|-------------------------|-------------------|
| cao:VariationUnit | cao:hasReading | cao:Reading |
| cao:VariationUnit | cao:hasBaseReading | cao:BaseReading |
| cao:VariationUnit | cao:hasSubvariationUnit | cao:VariationUnit |
| cao:BaseReading | rdfs:subclassOf | cao:Reading |



2.1. Creation of a new apparatus entry



Example

```
@prefix ex: <http://example.org/> .
@prefix cao: <https://w3id.org/cao/> .
@prefix crm: <http://www.cidoc-crm.org/cidoc-crm/> .
@prefix dcterms: <http://purl.org/dc/terms/> .
@prefix frbroo: <http://iflastandards.info/ns/fr/frbr/frbroo/> .
@prefix oa: <http://www.w3.org/ns/oa#> .
@prefix prov: <http://www.w3.org/ns/prov#> .
@prefix rdf: <http://www.w3.org/1999/02/22-rdf-syntax-ns#> .
@prefix rdfs: <http://www.w3.org/2000/01/rdf-schema#> .
@prefix xml: <http://www.w3.org/XML/1998/namespace> .
@prefix xsd: <http://www.w3.org/2001/XMLSchema#> .

# the scholarly annotation
<annotation/anno01> a oa:Annotation ;
  # the apparatus entry
  oa:hasBody <app/app01> ;
  # the variation point within the edition TEI document
  oa:hasTarget <varloc/vl01> ;
  # the scholar's identifier
  dcterms:creator <resp/fgiov> ;
  # the date on which the apparatus entry was created
  dcterms:created "2019-03-09"^^xsd:date .
```






2.2. the body of the annotation: the apparatus entry



| Domain | Property | Range |
|--------------------------------|--------------------------------------|--------------------------------|
| <code>cao:VariationUnit</code> | <code>cao:hasReading</code> | <code>cao:Reading</code> |
| <code>cao:VariationUnit</code> | <code>cao:hasBaseReading</code> | <code>cao:BaseReading</code> |
| <code>cao:VariationUnit</code> | <code>cao:hasSubvariationUnit</code> | <code>cao:VariationUnit</code> |
| <code>cao:BaseReading</code> | <code>rdfs:subclassOf</code> | <code>cao:Reading</code> |




2.2. the body of the annotation: the apparatus entry



| Domain | Property | Range |
|-------------------|-------------------------|-------------------|
| cao:VariationUnit | cao:hasReading | cao:Reading |
| cao:VariationUnit | cao:hasBaseReading | cao:BaseReading |
| cao:VariationUnit | cao:hasSubvariationUnit | cao:VariationUnit |
| cao:BaseReading | rdfs:subclassOf | cao:Reading |



2.2. the body of the annotation: the apparatus entry



```

# a unit of variation
<app/app01> a cao:VariationUnit ;
# the base reading
cao:hasBaseReading <rdg/anno01-rdg01> ;
# the variant readings
cao:hasReading <rdg/anno01-rdg02> ,
<rdg/anno01-rdg03> .

<rdg/anno01-rdg01> a cao:BaseReading ;
rdf:value "diffundi"^^xsd:string .

<rdg/anno01-rdg02> a cao:Reading ;
rdf:value "diffudit"^^xsd:string .


<rdg/anno01-rdg03> a cao:Reading ;
rdf:value "diffundit"^^xsd:string .

<app/a10> a cao:VariationUnit ;
cao:hasSubvariationUnit <app/a10-1> ,
<app/a10-2> .
  
```

| Domain | Property | Range |
|-------------------|-------------------------|-------------------|
| cao:VariationUnit | cao:hasReading | cao:Reading |
| cao:VariationUnit | cao:hasBaseReading | cao:BaseReading |
| cao:VariationUnit | cao:hasSubvariationUnit | cao:VariationUnit |
| cao:BaseReading | rdfs:subclassOf | cao:Reading |



2.3. the body of the annotation: classifying the readings by type and cause



Same function of the TEI

@type



@cause

cao:ReadingType and
cao:ReadingCause are
direct subclasses of
crm:E55_Type

| | | |
|-------------|---------------------|------------------|
| cao:Reading | cao:hasReadingType | cao:ReadingType |
| cao:Reading | cao:hasReadingCause | cao:ReadingCause |



2.3. the body of the annotation: classifying the readings by type and cause





Instances of `cao:ReadingType` are individuals

Each of them is matched with the corresponding entity of the LAWD (Linked Ancient World Data ontology <https://github.com/lawdi/LAWD>) reading classification through the property `owl:sameAs`.




2.3. the body of the annotation: classifying the readings by type and cause



```
<rdg/anno01-rdg03> a cao:Reading ;
  cao:hasReadingType cao:omission ;
  cao:hasReadingCause cao:homeoteleuton ;
  rdf:value ""^^xsd:string .
```





2.4. the body of the annotation: relating the readings to one another



| Domain | Property | Range |
|-------------------|---------------------|-----------------|
| cao:VariationUnit | cao:hasBaseReading | cao:BaseReading |
| cao:VariationUnit | cao:hasReading | cao:Reading |
| cao:BaseReading | cao:hasVariant | cao:Reading |
| cao:Reading | prov:wasRevisionOf | cao:Reading |
| cao:Reading | prov:wasDerivedFrom | cao:Reading |
| cao:Reading | cao:wasCorrectedTo | cao:Reading |
| cao:Reading | cao:follows | cao:Reading |



2.4. the body of the annotation: relating the readings to one another



```
<app/app08> a cao:VariationUnit ;
  cao:hasReading <rdg/anno08-rdg01> ,
  <rdg/anno08-rdg02> ,
  <rdg/anno08-rdg03> .


<rdg/anno08-rdg01> a cao:Reading ;
  cao:wasCorrectedTo <rdg/anno08-rdg02> ;
  cao:hasReadingType cao:deletion ;
  rdf:value "this"^^xsd:string .

<rdg/anno08-rdg02> a cao:Reading ;
  cao:wasCorrectedTo <rdg/anno08-rdg03> ;
  cao:hasReadingType cao:deletion ;
  rdf:value "such a"^^xsd:string .

<rdg/anno08-rdg03> a cao:Reading ;
  cao:hasReadingType cao:addition ;
  rdf:value "a"^^xsd:string .
```





2.5. the body of the annotation: describing the provenance of the readings



| Domain | Property | Range |
|------------------------|--------------------------|------------------------|
| cao:Reading | prov:wasAttributedTo | prov:Agent |
| cao:Reading | prov:wasGeneratedBy | hico:InterpretationAct |
| hico:InterpretationAct | prov:wasAssociatedWith | prov:Agent |
| hico:InterpretationAct | cao:hasInterpretedEntity | frbroo:F2_Expression |
| hico:InterpretationAct | hico:isExtractedFrom | frbroo:F2_Expression |



2.5. the body of the annotation: describing the provenance of the readings



Citing other scholars' readings

In TEI, @source is used to indicate responsibility to say that a witness supports a particular reading.


It contains a reference to an external source (a **published edition**).

In CAO, a cited reading is related to its original source by the property prov:hadPrimarySource.

```
<rdg/anno01-rdg02> a cao:Reading ;  
  rdf:value "diffudit"^^xsd:string ;  
  prov:hadPrimarySource <http://example.org> .
```



2.5. the body of the annotation: describing the provenance of the readings



Attributing a reading to a specific hand

TEI uses @hand;


CAO the property cao:hasAttributedHand.

Its domain is cao:Reading, its range is prov:Agent

```
<rdg/anno01-rdg02> a cao:Reading ;
  rdf:value "diffudit"^^xsd:string ;
  cao:hasAttributedHand <resp/m1> .
```



2.5. the body of the annotation: describing the provenance of the readings




Representing the interpretation act which generated a reading

cao:Readings --> acts of scholarly interpretation:
we use Classes and Properties from HiCO
(Historical Context Ontology)
(<https://marilenadaquino.github.io/hico/>).



2.5. the body of the annotation: describing the provenance of the readings



Historical Context Ontology:

“It addresses features characterising hermeneutical activities performed by scholars while generating new information (i.e. an interpretation act). It allows to represent and reason on reliability of argumentations around attributions, by evaluating features such as motivations, types of cited sources or criteria, dates, relations with other claims (e.g. agreement/disagreement)”.

“HiCO extends the PROV Ontology with terms for describing aspects of the hermeneutical activity, and reuses existing ontologies, such as CiTO Ontology for linking attributions to related sources.”

From <https://marilenadaquino.github.io/hico/>


See also PROV-O <https://www.w3.org/TR/prov-o/>

And CiTO

<https://sparontologies.github.io/cito/current/cito.htm>
!



2.5. the body of the annotation: describing the provenance of the readings



Representing the interpretation act which generated a reading

hico:InterpretationAct --> a process of scholarly interpretation, related to the responsible agent (prov:Agent) through the property prov:was AssociatedWith.

cao:Reading as result of an interpretation act. An interpretation act and a reading are associated through the property prov:wasGeneratedBy


| | | |
|-------------------------------|-------------------------------|-------------------------------|
| hico:InterpretationAct | prov:wasAssociatedWith | prov:Agent |
| cao:Reading | prov:wasGeneratedBy | hico:InterpretationAct |



2.5. the body of the annotation: describing the provenance of the readings

Representing the interpretation act which generated a reading

It's desirable to connect cao:Reading with the prov:Agent through the property prov:AttributedTo




To sum up:

| | | |
|-------------------------------|-------------------------------|-------------------------------|
| hico:InterpretationAct | prov:wasAssociatedWith | prov:Agent |
| cao:Reading | prov:wasGeneratedBy | hico:InterpretationAct |
| cao:Reading | prov:wasAttributedTo | prov:Agent |



2.5. the body of the annotation: describing the provenance of the readings



Reusing another scholar's reading

| | | |
|------------------------|----------------------|-----------------------------|
| cao:Reading | prov:wasAttributedTo | prov:Agent |
| hico:InterpretationAct | hico:isExtractedFrom | <u>frbroo:F2_Expression</u> |

Here Expression is a *published edition*


Conjecturing a new reading

| | | |
|-------------|--------------------------|-----------------------------|
| cao:Reading | prov:wasAttributedTo | prov:Agent |
| prov:Agent | cao:hasInterpretedEntity | <u>frbroo:F2_Expression</u> |

Here Expression is a *fragment of a witness*



2.6. the body of the annotation: from the reading to the text



FRBR model: (https://www.ifla.org/wp-content/uploads/2019/05/assets/cataloguing/frbr/frbr_2008.pdf)


WEMI

Work

Expression

Manifestation

Item




Texts reaches us in **multiple versions**.

Each textual version represents a **different realization** of the same **work**.

An **FRBR expression**, i.e. a text, is modelled using the FRBRoo class **F2 Expression**, which defines "*the specific intellectual or artistic form that a work takes each time it is realized*" ([IFLA 2009](#)).



2.6. the body of the annotation: from the reading to the text



```
<rdg/anno01-rdg01> a cao:BaseReading ;
  rdf:value "diffundi"^^xsd:string ;
  cao:isWitnessedBy <wit-frag/anno01-wfrag01> ,
  <wit-frag/anno01-wfrag02> .
```

```
<rdg/anno01-rdg02> a cao:Reading ;
  rdf:value "diffudit"^^xsd:string ;
  cao:isWitnessedBy <wit-frag/anno01-wfrag03> .
```

```
<rdg/anno01-rdg03> a cao:Reading ;
  rdf:value "diffundit"^^xsd:string ;
  cao:isWitnessedBy <wit-frag/anno01-wfrag04> .
```

```
<wit-frag/anno01-wfrag01> a frbroo:F23_Expression_Fragment ;
  frbroo:R15i_is_fragment_of <wit-expr/wexp01> .
```

```
<wit-frag/anno01-wfrag02> a frbroo:F23_Expression_Fragment ;
  frbroo:R15i_is_fragment_of <wit-expr/wexp02> .
```


A reading is a scholarly claim, the outcome of an act of interpretation, which is supported by a particular **fragment of a witness**, a **frbroo F23 Expression Fragment**.

The CAO property **cao:isWitnessedBy** relates a reading to an expression, i.e. to the text of the witness (either the full text or the specific textual fragment that supports the reading within a witness).

The property **frbroo:R15i is fragment of** connects an expression fragment to the expression to which it belongs.



2.6. the body of the annotation: from the text to the witness



Expressions cannot exist without a carrier.

A carrier is, in FRBR terms, a manifestation.


FRBRoo distinguishes between two classes of manifestation:

- **Manifestation Singleton**: belongs to the realm of physical things: it is a unique, physical object such as a manuscript, and cannot be replicated.
- **Manifestation Product Type**: an abstract notion, it comprehends publications and printed editions, which can exist in multiple physical copies.

| Domain | Property | Range |
|----------------------|--------------------------------|--------------------------------------|
| frbroo:F2_Expression | crm:P128i_is_carried_by | frbroo:F3_Manifestation_Product_Type |
| frbroo:F2_Expression | frbroo:R4_carriers_provided_by | frbroo:F4_Manifestation_Singleton |




2.6. the body of the annotation: from the reading to the witness



`frbroo:F2_Expression` is carried by
a physical document
(`frbroo:F4_Manifestation_Singleton`)
or an edition
(`frbroo:F3_Manifestation_Product_Type`).

To sum up:

A reading (`cao:Reading`) is a scholarly interpretation of a witness fragment (`frbroo:F23_Expression_Fragment`), that belongs to a witness (`frbroo:F2_Expression`).





2.7. the body of the annotation: philological notes

```
<rdg/a6-r1> a cao:BaseReading ;  
  crm:P3_has_note <note/a6-n1> ;  
  rdf:value "['Beowulfe']"^^xsd:string .  
  
<note/a6-n1> a crm:E62_String ;  
  rdf:value "['[...] Folio 179, with the last page (Fol. 198b)  
[...]']"^^xsd:string ;  
  crm:P2_has_type <https://www.example.org/type/philological> .
```

The property **crm:P3_has_note** links a reading or apparatus entry to a scholarly note.

The range of the property **crm:P3_has_note** is an rdfs:Literal.

It is possible to use **crm:P2_has_type** on the note to further characterize the type of annotation (a possible value is, e.g., 'philological').

(https://cidoc-crm.org/html/cidoc_crm_v7.1.1.html)



2.8. A special case of variation: transposition

Transposition occurs when text is transferred from one location to another.

As transposition involves a relationship between a transposed text and (at least) two distinct locations, its representation requires to link the annotation to multiple targets.


The transposed text is then related to the original and new location via the properties cao:wasTransposedFrom and cao:wasTransposedTo.

```
<annotation/anno02> a oa:Annotation ;  
  oa:hasBody <app/app02> ;  
  oa:hasTarget <varloc/v102> , <varloc/v103> ;  
  dcterms:creator <person/fgiovan> ;  
  dcterms:created "2019-03-09"^^xsd:date .
```

```
<rdg/anno02-rdg02> a cao:Reading ;  
  cao:hasReadingType cao:transposition ;  
  cao:wasTransposedFrom <varloc/v102> ;  
  cao:wasTransposedTo <varloc/v103> .
```




2.9 the target of the annotation: linking the critical apparatus to the text



- **Web Annotation Ontology**


- (<https://www.w3.org/TR/annotation-vocab/>)

- **Body**
- **Target**
- **Creator**
- **Date of Creation**

"the locus of variation in the critical text"



2.9 the target of the annotation: linking the critical apparatus to the text



Methods for linking the apparatus to the critical text:

1. *location-referenced* method
2. *double-end-point-attached* method
3. *parallel segmentation* method



2.9 the target of the annotation: linking the critical apparatus to the text

Parallel segmentation method:

Not compatible with an external apparatus: it does not impose the existence of a base text and for this it allows only an *inline markup*

But it allows the specification of the boundaries of the location of the variant in detail, through the use of empty elements equipped with unique identifiers.

Location-referenced method:

It can be used even when the critical apparatus is external.

Giving the exact location of the variant is not a requirement:

the readers reconstruct the exact location autonomously, once they have identified the relevant line as they would do with a print edition.



2.9 the target of the annotation: linking the critical apparatus to the text

Double-end-point-attached method:

It turns out to be the most suitable for linking the RDF critical apparatus to the text

```
... freta rapidisque <anchor xml:id="varloc-s01"/>diffundi<anchor  
xml:id="varloc-e01"/> ...
```

```
<varloc/v101> a cao:VariationLocation ;  
  oa:hasSource <https://example.org/example.xml> ;  
  oa:hasSelector [  
    a oa:RangeSelector ;  
      oa:hasStartSelector [  
        a oa:XPathSelector ;  
        rdf:value "//1/anchor[@xml:id='varloc-s01']" ] ;  
      oa:hasEndSelector [  
        a oa:XPathSelector ;  
        rdf:value "//1/anchor[@xml:id='varloc-e01']" ] ] ] .
```

It's used for linking the apparatus to a specific base text within the TEI document containing the edition, through the Web Annotation class

oa:RangeSelector,

defining the beginning and the end through the subclasses

oa:hasStartSelector


oa:hasEndSelector

using XPath expressions.



3. CAO Entities – An Overview


Class Hierarchy





3. CAO Entities – An Overview


Object Properties Hierarchy





3. CAO Entities – An Overview

Individuals





3. CAO Entities – An Overview

Data Types

Classes Object properties Data properties Datatypes Individuals


Datatypes:

- owl:rational
- owl:real
- rdf:langString
- rdf:PlainLiteral
- rdf:XMLLiteral
- rdfs:Literal
- xsd:anyURI
- xsd:base64Binary
- xsd:boolean
- xsd:byte
- xsd:dateTime
- xsd:dateTimeStamp
- xsd:decimal
- xsd:double
- xsd:float
- xsd:hexBinary
- xsd:int
- xsd:integer
- xsd:language
- xsd:long
- xsd:Name
- xsd:NCName
- xsd:negativeInteger
- xsd:NMTOKEN
- xsd:nonNegativeInteger
- xsd:nonPositiveInteger
- xsd:normalizedString
- xsd:positiveInteger
- xsd:short
- xsd:string
- xsd:token
- xsd:token
- xsd:unsignedByte
- xsd:unsignedInt
- xsd:unsignedLong
- xsd:unsignedShort



3. CAO Entities – An Overview

Data Properties





3. CAO Entities – An Overview

Annotation Properties


Annotation property hierarchy:

- cachedSource
- dc:contributor
- dc:creator
- dc:date
- dc:description
- dc:rights
- dc:title
- dcterms:creator
- dcterms:description
- dcterms:license
- dcterms:modified
- foaf:name
- hasBody
- hasScope
- hasSource
- hasTarget
- owl:backwardCompatibleWith
- owl:deprecated
- owl:incompatibleWith
- owl:priorVersion
- owl:versionInfo
- preferredNamespacePrefix
- preferredNamespaceUri
- rdfs:comment
- rdfs:isDefinedBy
- rdfs:label
- rdfs:seeAlso
- renderedVia
- was revision of (prov:wasRevisionOf)**



3. CAO Entities – An Overview

OWLWiz Class-Tree





4. Conclusions

- The first ontology specifically created for representing scholarly digital editions' critical apparatus.
- A project which is part of a bigger one: *LIFT* (*Linked Data From TEI*) <https://projects.dharc.unibo.it/lift/> .
- Space for further researches.



4. Conclusions

- What to improve?
 - Version 0.9.
 - Correct some transcription errors.
 - Improve the representation of *transposition*.
 - Create a specific SPARQL endpoint.
 - Try to implement scholarly digital editions in order to test the CAO.



5. Bibliography

- **Giovannetti F. 2015**

Combining TEI and Semantic Web Technologies to Annotate and Explore the Notebook of Paolo Bufalini (1915-2001).

- **Giovannetti F. 2019**

The Critical Apparatus as a Semantic Graph. A Combined Approach to Describing Textual Variation by TEI, RDF, and Ontologies



6. Web Pages

- CAO: <https://w3id.org/cao>
- PROV-O: <https://www.w3.org/TR/2013/REC-prov-o-20130430/>
- HiCO: <https://marilenadaquino.github.io/hico/>
- FRBR:
<https://fgiovannetti.github.io/cao/#http://iflastandards.info/ns/fr/frbr/frbroo/R4>
- OA: <https://www.w3.org/TR/annotation-vocab/#classes>



7. Credits and contacts

- Francesca Giovannetti: francesc.giovannett6@unibo.it
- Diego Canali: diego.canali@studio.unibo.it

Thank you for the attention



Diego Canali for TALOS – AI4SSH
ERA Chair in Artificial Intelligence for Humanities and Social Sciences
Rethymno, 6 November 2023